



TECHNICAL DATA SHEET: **SUBLITACK KR 100**

Coated sublimation paper for digital printing with water-based sublimating ink

TECHNICAL SPECIFICATIONS

- WEIGHT	95 gsm/sqm
- THICKNESS	110 my
- ROLLS LENGTH	120 mt
- AVAILABLE WIDTHS	91,4 - 111,8 - 132 - 162 cms
- INNER ROLL DIAMETRE	3"
- UTILISATION	transfer on all polyester fabrics: technical fabrics, banner, flags, sportswear Particularly suitable for transfer with press
- APPLICATION TEMPERATURE	it changes according to the fabric and we suggest to test the paper before using it. Generally, the application temperature is 195-205°C for 45-60 seconds
- QUALITY	good drying time very good value for money very good colour releasing no ghost effect after transfer no fabric tightening, thanks to the adhesive paper properties

STORAGE

- Keep dry
- It's suggested the utilisation in environment with a moisture of 45% and 23°C
- It's suggested to leave the paper without packing before using it
- Duration: 2 years if stocked in proper conditions and in the original packing

PARTICULAR EQUIPMENTS AVAILABLE ON REQUEST

VIRAX BORGHI ITALIA S.R.L.

Sede: Via Edison, 2 20090 Segrate (MI) - Tel. 02 26922041 - virax@virax.it

Filiale Veneto: Via dell'Artigianato, 13 31033 Castelfranco Veneto (TV) - Tel. 0423 720155

Filiale Centro Italia: Z.na Industriale Vallecupa 64010 Colonnella (TE) - Tel. 0861 749563

Filiale Toscana: Via Provinciale di Mercatale, 140 50059 Vinci (FI) - Tel. 335 6570468